# Electrical

05/10/2016

## CABLE TIE KAUFMANN



| | |
|---|---|
| AO763/0001<br>92X2.6MM PT1 | 1 |
| AO763/0002<br>140X3.6MM PT2 | 1 |
| AO763/0003<br>197X9MM PT3 | 1 |
| AO763/0004<br>267X4.8MM PT4 | 1 |
| AO763/0005<br>381 X 4.9MM PT5 | 1 |

Black positive locking quality cable ties, various lengths, pre-packed.

## LANTERN 15 LED SOLAR RECHARGEABLE




| | |
|---|---|
| V0600220 | 1 |

This classical styled solar lantern is ideal for the lapa or around the campsite and during power outages. The eco friendly solar technology draws energy from the sun and stores it in a rechargeable battery. Charging time approx: 6-8hrs in direct sunlight. Light is also dimible and will nurn for approx: 4-6hrs. Height: 240mm

## LAMP HALOGEN GU10 50W ALUM BP EUROLUX




EU-G96BP
Candela 800 Lifetime 2000 hrs 2700K

## LAMP HALOGEN MR16 50W LOOSE EUROLUX



EU-G97
Candela 1500 Lifetime 3000 hrs 2700K

## LAMP HALOGEN MR16 50W CLOSED EUROLUX



EU-G243
Candela 1450 Lifetime 3000 hrs 2700K

## LAMP REFLECTOR R50 40W E14 EUROLUX




EU-G74
Candela 380 Lifetime 1000 hrs 2700K

## LAMP PAR30 CLEAR 75W EUROLUX



EU-G170
Candela 1089 Lifetime 1000 hrs 2700K

## LAMP QI HALOGEN 120W 78MM LOOSE EUROLUX



EU-G249
2200lms Lifetime 2000 hrs 2900K

## LAMP REFLECTOR R63 60W E27 EUROLUX



EU-G75
Candela 920 Lifetime 1000 hrs 2700K

## LAMP PAR38 INFRARED 175W EUROLUX



EU-G204
Lifetime 3000 hrs Speciality Lamp

## LAMP QI HALOGEN EUROLUX




EU-G401BP
2200lms Lifetime 2000 hrs 2900K

EU-G403BP
2400lms Lifetime 2000 hrs 2900K

## GLOBE PAR38 CHICKEN SICCA THERM



| | |
|---|---|
| HW2675142<br>250W | 1 |

Incandescent lamp, PAR 38 type screw in fitting, infra red for use as chicken brooder light.

**LAMP MERCURY VAPOUR 250W EUROLUX**



EU-G103
12500lms Lifetime 10 000 hrs 4100K

**LAMP HP SODIUM E40 150W CLEAR EUROLUX**



EU-G118
13500lms Lifetime 20 000 hrs 2100K

**LAMP HALOGEN MR16 50W 10P EUROLUX**




EU-G505
Candela 1500 Lifetime 3000 hrs 2700K

**LAMP CFL SPIRAL 12W E27 YELLOW EUROLUX**




EU-G433Y
300lms Lifetime 6000 hrs

**LAMP HP SODIUM E40 400W OPAL EUROLUX**



EU-G114
45600lms Lifetime 20 000 hrs 2100K

**LAMP PAR38 80W RED EUROLUX**



EU-G171RD
Lifetime 1000 hrs

**LAMP CFL SPIRAL 12W B22 CW BP EUROLUX**




EU-G429BP
600lms Lifetime 6000 hrs 4000K

**LAMP CFL SPIRAL 12W B22 GREEN EUROLUX**




EU-G434GN
431lms Lifetime 6000 hrs

**LAMP HP SODIUM E40 400W CLEAR EUROLUX**



EU-G116
48000lms Lifetime 20 000 hrs 2100K

**LAMP HALOGEN GU10 50W GLASS EUROLUX**



EU-G186
Candela 800 Lifetime 2000 hrs 2700K

**TUBE FLUORESCENT 35W 1200MM EUROLUX**



EU-G43

**LAMP CFL SPIRAL 12W B22 RED EUROLUX**




EU-G434RD
100lms Lifetime 6000 hrs

**LAMP CFL 11W 3U B22 CW EUROLUX**



EU-G6
550lms Lifetime 6000 hrs

**LAMP REFLECTOR CFL R80 10W CW EUROLUX**




EU-G375
300lms Lifetime 6000 hrs 4200K

**LAMP PAR38 CFL 18W E27 CW EUROLUX**



EU-G213
500lms Lifetime 6000 hrs 4200K

**LAMP CANDLE CFL 3W B22 WW BP EUROLUX**




EU-G17BP
105lms Lifetime 6000 hrs

**LAMP INSECT KILLER 20W BP EUROLUX**



EU-G315BP

**LAMP CANDLE CFL 3W E27 WW BP EUROLUX**




EU-G18BP
105lms Lifetime 6000 hrs

**LAMP CFL 15W B22 DAY/NIGHT EUROLUX**




EU-G228
800lms Lifetime 6000 hrs 4000K

**LAMP CFL 15W 3U E27 WW EUROLUX**



EU-G160
800lms Lifetime 6000 hrs 2700K

**LAMP CFL 9W 3U E14 WW EUROLUX**



EU-G353
450lms Lifetime 6000 hrs 2700K

**LAMP GOLFBALL CFL 5W B22 WW BP EUROLUX**




EU-G20BP
200lms Lifetime 6000 hrs 2700K

**LAMP CFL 15W 3U E27 CW EUROLUX**



EU-G3
800lms Lifetime 6000 hrs 4000K

**LAMP CFL 11W 3U E27 WW EUROLUX**



EU-G162
550lms Lifetime 6000 hrs

**LAMP CFL 9W 12V DC E27 EUROLUX**



EU-G12
1155lms Lifetime 6000 hrs 4000K

**LAMP LED 4W GOLFBALL B22 WARM WHITE EUROLUX**




EU-G934
340lms Lifetime 30 000 hrs 3000K

**LAMP CFL SPIRAL 12W E27 BLUE EUROLUX**



EU-G433BL
50lms Lifetime 6000 hrs

**LAMP CFL 11W B22 DAY/NIGHT CW EUROLUX**




EU-G396
550lms Lifetime 6000 hrs

**LAMP LED A65 10W B22 COOL WHITE EUROLUX**




EU-G925
485lms Lifetime 30 000 hrs 4000K

**LAMP LED 4W GOLFBALL E14 WARM WHITE EUROLUX**




EU-G935
340lms Lifetime 30 000 hrs 3000K

**LAMP CFL SPIRAL 12W E27 GREEN EUROLUX**




EU-G433GN
250lms Lifetime 6000 hrs

**LAMP CFL SPIRAL 12W B22 YELLOW EUROLUX**




EU-G434Y
500lms Lifetime 6000 hrs

**LAMP LED A60 6W E27 COOL WHITE EUROLUX**




EU-G927
485lms Lifetime 30 000 hrs 4000K

**LAMP LED R50 5W E14 WARM WHITE 3000K EUROLUX**




EU-G938
350lms Lifetime 30 000 hrs 3000K

**LAMP PAR38 CFL 18W E27 WW EUROLUX**



EU-G23
500lms Lifetime 6000 hrs 2700K

**LAMP CFL 11W 3U E27 CW EUROLUX**



EU-G5
550lms Lifetime 6000 hrs

**LAMP SPIRAL R24W7S 24W CW EUROLUX**




EU-G620BP
960lms Lifetime 6000 hrs 4000K

**LAMP INSECT KILLER 6W BP EUROLUX**




EU-G316BP

**LAMP CFL 9W 3U B22 CW EUROLUX**



EU-G351
450lms Lifetime 6000 hrs 4000K

**LAMP PAR38 CFL E27 GREEN EUROLUX**



EU-G181GN
700lms Lifetime 6000 hrs

**LAMP PL 26W 4PIN CW EUROLUX**




EU-G630
1800lms Lifetime 8000 hrs 4200K

**LAMP TUBE 2D 16W 2PIN EUROLUX**




EU-G32
1030lms Lifetime 8000 hrs Cool White

**LAMP GOLFBALL CFL 5W E27 WW BP EUROLUX**




EU-G19BP
200lms Lifetime 6000 hrs 2700K

**LAMP PAR38 CFL E27 RED EUROLUX**



EU-G181RD
400lms Lifetime 6000 hrs

**LAMP LED GU10 7W DIMMABLE LAMP WW 3000K EUROLUX**




EU-G728WW
450lms Lifetime 30 000 hrs 3000K

**LAMP CFL 20W 3U B22 WW EUROLUX**



EU-G330
1155lms Lifetime 6000 hrs 4000K

**LAMP CFL 45W 4U E27 CW EUROLUX**



EU-G163
1155lms Lifetime 6000 hrs 4000K

**LAMP LED A65 10W E27 WARM WHITE EUROLUX**




EU-G922
850lms Lifetime 30 000 hrs

**LAMP LED A65 10W E27 COOL WHITE EUROLUX**




EU-G923
850lms Lifetime 30 000 hrs 4000K

**LAMP LED A60 6W B22 WARM WHITE EUROLUX**




EU-G928
485lms Lifetime 30 000 hrs 3000K

**LAMP LED 4W CANDLE E27 WARM WHITE EUROLUX**




EU-G930
340lms Lifetime 30 000 hrs 3000K

**LAMP CFL PL 9W CW BP EUROLUX**




EU-G130
450lms Lifetime 8000hrs 4000K

**LAMP LED A60 B22 DAY/NIGHT 8W CW EUROLUX**




EU-G762CW
485lms Lifetime 30 000 hrs 6000K

**FLUOR STARTERS**




HW2675307 5
80W FSU4

Ignites the fluorescent tube by sending an electrical current through the fluorescent tube for the gases to burn.

**CHOKE BALLAST**




HW2675328 1
65W 5FT 1L

Used for rapid start fluorescent tubes and not switch start lamps, absorbs a electrical current and send a constant electrical current through the fluorescent tube for the gas to ignite.

**FITTING FLUORESCENT 1X58W 5FT EUROLUX**



EU-PR38
IP : 20 Epoxy Coated Pressed Steel

**FITTING FLUORESCENT 2X18W 2FT EUROLUX**



EU-PR39
IP : 20 Epoxy Coated Pressed Steel

**FITTING FLUORESCENT 2X36W 4FT EUROLUX**



EU-PR40
IP : 20 Epoxy Coated Pressed Steel

**FITTING FLUORESCENT 2X58E 5FT EUROLUX**



EU-PR41
IP : 20 Epoxy Coated Pressed Steel

**LIGHT TURBO 1LIGHT ROUND BASE EUROLUX**



EU-S40W
IP 20 Steel D165mm D80mm

### LIGHT TURBO 2LIGHT ROUND BASE EUROLUX



EU-S43W
IP 20 D 180mm D 240mm

### LIGHT TURBO 3LIGHT ROUND BASE EUROLUX



EU-S45W
LIGHT TURBO 3LIGHT ROUND BASE

### SPIKE GARDEN PLASTIC MR16 EUROLUX



EU-O113
IP 65 H 400mm D 75mm

### LAMP GALLERY F/GLASS & F/G



| | |
|---|---|
| HW2672045 | 1 |
| BC 160MM | |
| HW2672049 | 1 |
| BC 200MM | |

Ceiling bayonet type Lamp holder mounting piece manufactured from fibre glass with fibreglass Lamp holder accommodating 40 to 100 W incandescent lamps.

### LIGHT CENTURION



| | |
|---|---|
| HW2672150 | 1 |
| 2D 16WT OPAL | |

Modern slimline multipurpose energy saver fitting. UV stabilised polycarbonate lens. 2D 16Watt lampholder. Opal colour. Suitable for indoor and outdoor use. Use with 2D globe HW2675130. Complete with stainless steel fixing screws. SABS approved. IP 65 weather proof rating. Lightfitting size 270mm x 60mm.


### LIGHT CEILING WITHOUT GLOBE



| | |
|---|---|
| HW2672083 | 1 |
| BC 60W 160MM | |

Ceiling lamp holder mounting piece manufactured from PVC with nylon Lamp holder accommodating 40 to 60 W incandescent lamps, complete with 60 W incandescent lamp. Functions when installed in a vertical position.

### LIGHT RECTANGULAR ALUM BASE



| | |
|---|---|
| HW2672148 | 1 |
| BC 100W WHT | |

Modern industrial bulkhead light fitting. High visor, rectangular light. UV stabilised, polycarbonate lens with white die cast aluminium powder coated base. BC 220v lamp holder. Clear see through lens. Suitable for indoor, outdoor and industrial use. Ideal for agricultural application. Use with BC type globe. Splash proof. Complete with BC light fitting with a robust lens. SABS approved. IP55 Weather proof rating. Light size 235mm x 115mm. Should be fitted by an approved electrician. Bulkhead with polycarbonate lens can be used to burn continuously.

### LIGHT ROUND ALUM BASE



| | |
|---|---|
| HW2672140 | 1 |
| BC 100W WHT | |

Modern industrial bulkhead light fitting. High visor round light. UV stabilised, polycarbonate lens with white die cast aluminium powder coated base. BC 220V lamp holder. Clear see through lens. Suitable for indoor, outdoor and industrial use. Ideal for agricultural application. Use with BC type globe. Splash proof. Complete with BC light fitting. SABS approved. Robust lens. IP55 Weather proof rating. Light size: 190mm x 115mm. Should be fitted by an approved electrician. Bulkhead with polycarbonate lens can be used to burn continuously.

### LAMP GALLERY PVC & NYLON



| | |
|---|---|
| HW2672059 | 1 |
| BC 160MM | |
| HW2672062 | 1 |
| BC 200MM | |

Ceiling lamp holder mounting piece manufactured from PVC with nylon lamp holder accommodating 40 to 60W incandescent lamps.

### LIGHT OUTDOOR FLOOD



| | |
|---|---|
| HW2672123 | 1 |
| 2X18W 230V | |

Superior quality 36W 230V energy saving casted steel base outdoor flood light fitting. Uses two 18W 220-230V compact fluorescent lamps with PL11 base. Spare globe HW2675162. Globes not included. Matching globe at code HW2675159.

### LIGHT BATHROOM ALAB 230MM EUROLUX



EU-C8A
IP 20 Depth 85mm Diameter 220mm Steel

### LIGHT CHEESE FITTING ROUND EUROLUX



EU-C95O
IP 20 Depth 100mm Diameter 250mm Steel

### DOWNLIGHT SET 3PACK STRAIGHT WHITE EUROLUX



EU-D63W
IP : 22 Includes 3 x Halogen GU10 50W

### BULKHEAD ROUND HALF LENS SMALL EUROLUX



EU-B56B
Black die cast aluminium with frosted glass

### BULKHEAD OVAL SMALL EUROLUX



EU-B59B
IP : 54. Class : 1

### HEATER BATHROOM 2 LAMPS EUROLUX



EU-C85W
IP : 20 Plastic/Glass 3 in 1 bathroom

### LIGHT CHEESE FITTING SQUARE EUROLUX



EU-C96O
IP 20 Steel H 250mm W 250mm D 100mm

### LIGHT EMPEROR MATELEC OPAL




HW2672158 1
2DX28W

Energy saving light fitting ideal for outdoor use. Suited for all weather conditions. Suited for 2D X 28 W energy saver lamp.

### LIGHT MIRAGE VISOR ES MATELEC CLEAR




HW2672152 1

Energy saving light fitting ideal for outdoor use. Suited for all weather conditions. Suited for E27 energy saver lamp with screw base.

### LIGHT BABY EMPEROR ES MATELEC OPAL




HW2672153 1

Energy saving light fitting ideal for outdoor use. Not reccomended for use in housing estates. Lamp can easily be removed without loosening screw's. Suited to all weather conditions. Suited for E27 energy saver lamp with screw base.

### LIGHT CENTURION HIGH VISOR ES MATELEC CLEAR




HW2672155 1

Energy saving light fitting ideal for outdoor use. Stainless steel screws. Heavy duty construction. Suited for all weather conditions. Suited for E27 energy saver lamp with screw base.

### BULKHEAD RECTANGULAR BLACK EUROLUX



EU-B111B
Rustproof IP: 44 Class 2.

### BULKHEAD ROUND LARGE EUROLUX



EU-B42B
Black die cast aluminium with frosted glass

### BULKHEAD ROUND GRID SMALL EUROLUX



EU-B53B
Black die cast aluminium with frosted glass

### BULKHEAD ROUND SMALL EUROLUX



EU-B55B
IP : 54. Class : 1

### LIGHT CEILING FLORAL PATERN EUROLUX



EU-C396
IP 20 Depth 8mm Diameter 300mm Steel

### LIGHT CEILING ALAB 300MM E27 EUROLUX



EU-C48SC
IP 20 Depth 85mm Diameter 300mm Steel

### HEATER BATHROOM 4 LAMPS EUROLUX



EU-C86W
IP : 20 Plastic/Glass 3 in 1 bathroom

### LAMP HOLDER BATTEN NYLON BC



HW2682121 1

Bayonet type 25mm Lamp holder accommodating 40 to 200 W incandescent lamps manufactured from nylon material - used for surface mount on various surfaces.

### LAMP HOLDER BRASS BC




HW2682125 1

Bayonet type 25mm Lamp holder accommodating 40 to 200W incandescent lamps manufactured from brass - used for surface mount on various surfaces.

### LAMP HOLDER ILLUMINATION SABS BC



HW2681989 1

Edison type lamp holder accommodating 40 to 200W incandescent lamps manufactured from nylon material used directly with cord cable. Typically used with coloured globes. Cable at HW2679043 and HW2679043P.

### LAMP HOLDER PAR 38 DOUBLE WALL MOUNT



HW2682132 1

Lamp holder accommodating two Par 38 incandescent lamps (HW2675175, HW2675179)manufactured from nylon - used for surface mount on various surfaces.

### SWITCH LIGHT 2L CBI



HW2682317 1

Flush mounted light switch to connect or disconnect a circuit.

### LIGHT FITTING QIHAL.GLASS & SENSOR



HW2673130 1
150W

Weatherproof light fitting accommodating 150w QI halogen lamp, includes a movement detecting sensor with a integrated day night switch relay, switching the lamp on and off.

### LIGHT SECURITY QI HALOGEN WITH GLASS



HW2672007 1
150W 118MM
HW2672018 1
500W 118MM

QI Halogen lamp fitting with protection glass, used for security lighting and available for various wattage. Halogen globes at HW2675103, HW2675121, HW2675176 (not included).

### FLOODLIGHT WITH GLASS 120W EUROLUX



EU-FS13B
IP : 55 Die Cast Aluminium

### LANTERN 4 PANEL DOWN BLACK EUROLUX



EU-O17B
IP : 44  H 380mm W 150mm D 185mm

### CONDUIT BOX 2 WAY ANGLE SABS



| | |
|---|---|
| HW2685085 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations. Loose.

### SCRUITS



| | |
|---|---|
| HW2685569 | 1 |
| LARGE PP100 | |

Porcelain wire connector from 1.5 to 6mm copper housewire.

### WORKLIGHT TELESCOPIC 2X500W EUROLUX



EU-FS4
IP : 44 H 1890mm W 710mm D 580mm

### CONDUIT NORMAL BEND SABS



| | |
|---|---|
| HW2685469 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations. Loose.

### CONDUIT BOX 2-WAY THROUGH SABS



| | |
|---|---|
| HW2685124 | 1 |
| 20MM | |

To further route the wiring to its required termination/s.

### WALL BOX PAINTED



| | |
|---|---|
| HW2684913 | 1 |
| 100X50MM | |
| HW2684924 | 1 |
| 100X100MM | |

Flush mount wall box, manufactured from cold rolled sheets and painted silver, accommodates all flush mount switches and plugs.

### FLOODLIGHT 500W WITH SENSOR EUROLUX



EU-FS9B
IP : 44 Aluminium

### CONDUIT INSPECTION ELBOW SABS



| | |
|---|---|
| HW2685507 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations, with an inspection lid which can be removed to inspect the electrical wiring. Loose.

### CONDUIT BOX 8 WAY PVC



| | |
|---|---|
| HW2685218 | 1 |

Used to re-route electrical wiring to its required terminations. Loose.

### WALL BOX PVC



| | |
|---|---|
| HW2685023 | 1 |
| 100X50MM | |
| HW2685027 | 1 |
| 100X100MM | |

Surface mount wall box, manufactured from PVC, accommodates all flush mount switches and plugs. Loose.

### SWITCH BOX WATERPROOF (BOX ONLY)



| | |
|---|---|
| HW2683556<br>100X50MM | 1 |

Weatherproof box accommodating flush mount wall plug with switch to connect/disconnect a circuit for appliances with a maximum load of 15A.


### COVER PLATE BLANK



| | |
|---|---|
| HW2682861<br>100X50MM | 1 |
| HW2682867<br>100X100MM | 1 |

Cover plate to protect a wiring termination point.

### CIRCUIT BREAKER 2.5KA 1PHASE SAM



| | |
|---|---|
| HW2684103<br>10A | 1 |
| HW2684109<br>15A | 1 |
| HW2684112<br>20A | 1 |
| HW2684115<br>25A | 1 |
| HW2684118<br>30A | 1 |
| HW2684121<br>40A | 1 |
| HW2684123<br>45A | 1 |
| HW2684125<br>50A | 1 |

Hydraulic magnetic mini circuit breaker for the protection of domestic appliances and distribution panel circuits. Loose.

### CIRCUIT BREAKER 2.5KA 3PHASE SAM



| | |
|---|---|
| HW2684131<br>15A | 1 |
| HW2684136<br>20A | 1 |
| HW2684143<br>30A | 1 |
| HW2684148<br>40A | 1 |
| HW2684152<br>50A | 1 |

Hydraulic magnetic mini circuit breaker for the protection of domestic appliances and distribution panel circuits. Loose.

### CIRCUIT BREAKER 13MM 3KA 1PHASE LEAR



| | |
|---|---|
| HW2682891<br>6A | 1 |
| HW2682893<br>10A | 1 |
| HW2682894<br>16A | 1 |
| HW2682895<br>20A | 1 |
| HW2682897<br>25A | 1 |
| HW2682898<br>32A | 1 |

Single phase circuit breakers.Complies with SABS and NRCS regulations.

### CIRCUIT BREAKER 19MM 3KA 1PHASE LEAR



| | |
|---|---|
| HW2682880<br>16A | 1 |
| HW2682881<br>20A | 1 |
| HW2682882<br>25A | 1 |
| HW2682884<br>32A | 1 |
| HW2682885<br>40A | 1 |
| HW2682886<br>50A | 1 |
| HW2682888<br>63A | 1 |

Single phase circuit breakers. Complies with SABS and NRCS regulations.


### MULTIMETER DIGITAL




| | |
|---|---|
| HW2661023<br>AC DC 2-500V | 1 |

DT830 series multi function tester, complete with leads and free battery. Unit is protected with fuse. Auto polarity indicator, overrange indicator and low battery indicator. Use for DC current measurement, DC Voltage measurement, AC Voltage measurement, resistance measurement, temperature measurement, transistor testing, diode and continuity measurement, test signal output and battery measurement.

### SWITCH DAY/NIGHT 15AMP




| | |
|---|---|
| HW2684308 | 1 |

Used for the automatic control of lighting at predetermined light levels, thus eliminating the need for a time switch or manual switching.

### SWITCH TIME PLUG 24 HOURS



| | |
|---|---|
| HW2684316 | 1 |

Fits into a normal 16A switch socket, used for switching appliances such as lights, tv, radio at predetermined times. 220/250 volt AC 50/60 Hz power supply.

### SENSOR MOVEMENT MICROWAVE MATELEC




HW2684309 1

Compact movement sensor for indoor use. Conveniently switches your light on and off for you by means of movement detection. Sensitivity adjustment from 2 to 16 M.

### CIRCUIT BREAKER ISOLATOR 38MM 4.5KA 2PHASE




HW2682904 1
63A

A non-automatic flushed circuit breaker and used as geizer disconnector. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### ISOLATOR SWITCH 2PHASE 100 X 100 LEAR



HW2682848 1
60A

A non-automatic flushed circuit breaker and used as geizer disconnector. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### EARTH LEAKAGE 38MM 3KA 2FASE




HW2682890 1
63A

An automatic switching device capable of sensing earth leakage currents. Also capable of interrupting overloads after a defined time period.

### ISOLATOR SWITCH 2PHASE 50 X 100 LEAR



HW2682847 1
60A

A non-automatic flushed circuit breaker and used as geizer disconnector. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### ISOLATOR INDUSTRIAL WITH BOX



HW2684256 1
30A 83MMX183MM

A non-automatic circuit breaker and can be used as switch disconnectors. It is fully rated and carries the associated circuit breaker fault current for 10 ms. Complete with 75mm x 75mm x 50mm steel box.

### ISOLATOR STOVE CRABTREE



HW2684241 1
60A

A non-automatic flushed circuit breaker and can be used as stove disconnectors. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### ISOLATOR GEYSER 1L 2PHASE D/PL



HW2684247 1
30A

A non-automatic flushed circuit breaker and used as geizer disconnector. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### ISOLATOR STOVE CBI




HW2684265 1
2POLE 4X4 WHITE

A non-automatic flushed circuit disconnector and used as stove isolator.


### ISOLATOR GEYSER CBI



HW2684266 1
2POLE 4X2 WHITE

A-non-automatic flushed circuit breaker and used as geyser disconnector. It is fully rated and carries the associated circuit breaker fault current for 10ms.

### DISTRIBUTION BOARD SURFACE SAM



HW2684427 1
6MOD

HW2684431 1
8MOD

HW2684435 1
10MOD

HW2684439 1
12MOD

HW2684442 1
16MOD

Surface mount distribution board accommodating electrical switchgear mounted on mini rail.

### READY BOARD COMPLETE WITH LIGHT



HW2682360 1
13A

HW2682361 1
16A

Ready board complete with 3 switches, circuit breakers, earth leakage and light. Ideal for use in RDP housing projects as well as in garages, wendy houses, lapas and caravans. Available in 16A for RSA and 13A for Botswana.

### METER BOX



| | |
|---|---|
| HW2684375<br>305X460X230MM12X18X9 | 1 |
| HW2684457<br>460X460X230MM18X18X9 | 1 |

General-purpose weatherproof steel enclosure, with a masonite equipment mounting board at the back. Used for the protection of equipment such as electrical meters.

### FISH TAPE ELECTRICIANS



| | |
|---|---|
| HW2660000<br>30M | 1 |

Tempered and hardened spring steel blade used for pulling electrical cable through conduit.

### STRIP CONNECTOR



| | |
|---|---|
| HW2660283<br>5 AMP 12WAY | 1 |
| HW2660289<br>15 AMP 12WAY | 1 |
| HW2660293<br>30 AMP 12WAY | 1 |

For connecting and termination of various cable sizes.

### CABLE ELECTRIC PVC



| | |
|---|---|
| HW2679183<br>RED 1.5MM 100 (PM) | 100 |
| HW2679221<br>BLACK 1.5MM 100M (PM) | 100 |
| HW2679232<br>BLUE 1.5MM 100M (PM) | 100 |
| HW2679239<br>GREEN/YELL 1.5MM 100M (PM) | 100 |
| HW2679245<br>WHITE 1.5MM 100M (PM) | 100 |
| HW2679251<br>RED 2.5MM 100M (PM) | 100 |
| HW2679258<br>BLACK 2.5MM 100M (PM) | 100 |
| HW2679263<br>BLUE 2.5MM 100M (PM) | 100 |
| HW2679270<br>GREEN/YELL 2.5MM 100M (PM) | 100 |
| HW2679276<br>WHITE 2.5MM 100M (PM) | 100 |
| HW2679282<br>RED 4.0MM 100M (PM) | 100 |
| HW2679289<br>BLACK 4.0MM 100M (PM) | 100 |
| HW2679293<br>BLACK 6MM 100M (PM) | 100 |
| HW2679302<br>RED 1.5MM 20M | 1 |
| HW2679309<br>BLACK 1.5MM 20M | 1 |
| HW2679317<br>GRN/YELL 1.5MM 20M | 1 |
| HW2679325<br>RED 2.5MM 20M | 1 |
| HW2679331<br>BLACK 2.5MM 20M | 1 |
| HW2679358<br>RED 1.5MM 50M | 1 |
| HW2679359<br>BLACK 1.5MM 50M | 1 |
| HW2679360<br>GREEN 1.5MM 50M | 1 |
| HW2679363<br>BLUE 1.5MM 50M | 1 |
| HW2679365<br>RED 2.5MM 50M | 1 |
| HW2679369<br>BLACK 2.5MM 50M | 1 |
| HW2679370<br>GREEN 2.5MM 50M | 1 |
| HW2679371<br>BLUE 2.5MM 50M | 1 |

High conductivity annealed stranded copper wire, insulated with general purpose grade PVC in plain colours. General purpose house wire.

### CABLE CABTYRE 3 CORE PACK



| | |
|---|---|
| HW2680729<br>WHITE/WIT 1.0MM 30M PACK | 1 |
| HW2680730<br>BLACK/SWART 1.0MM 30M | 1 |
| HW2680733<br>WHITE/WIT 1.5MM 30M | 1 |
| HW2680734<br>BLACK/SWART 1.5MM 30M | 1 |
| HW2680737<br>WHITE/WIT 2.5MM 30M | 1 |
| HW2680738<br>BLACK/SWART 2.5MM 30M | 1 |

High conductivity bunched copper conductors, insulated and colour-coded with general-purpose flexible grade PVC. Already pre-packed in different lengths to eliminate shrinkage and theft.

### ELEMENT GEYSER WITH THERMOSTAT SOCKET



| | |
|---|---|
| HW2682732<br>2KW 100L | 1 |
| HW2682739<br>3KW 150L | 1 |
| HW2682743<br>4KW 200L | 1 |

Single circuit heating element for domestic hot water cylinders. It incorporates a pocket to accept the VKF type thermostat. Used in "normal" or non-aggressive water. Available in bulk and prepacks.

### ELEMENT GEYSER HARD WATER KAUFMANN PP1



Single circuit heating elementspecially designed for areas where water supply is hard and corrosive and where standard copper sheathed elements are not suitable. The sheath material is Incoly 825, which has a corrosion resistance musch superior.

### PLUGTOP MULTI EURO ADAPTOR ILLUMINATED 2X16A



| | |
|---|---|
| HW2680824 | 1 |

Crabtree slimline compact plugtop for domestic use. The plugtop is used together with the adaptor HW2681529, HW2681530, HW2681531. This product is of high quality. Voltage: 220V. Product colour: exterior body white. SABS approved. The benefits of the new plug can be enjoyed with the matching range of adapters, without having to replace excisting wall sockets. In addition to its space-saving benefits and superior looks, the new compact 3-pin plug is very user-friendly.


### PLUGTOP PVC



| | |
|---|---|
| HW2680823<br>16A | 2 |

16A three-pin appliance connector. Manufactured from PVC, top screw fixed.

**PLUGTOP BOTSWANA**



HW2681564 1
PLASTIC 3PIN 13A FUSED

13A Three-pin appliance connector for international use. Manufactured from PVC, top screw fixed.

**PLUGTOP CONVERTOR EUROMATE HEX 2X5A**



HW2681573 1
23X5A

Converting a two point 5A plug to a three pin connector.

**PLUGTOP SNAPPER**



HW2680827 1
16A

16A three-pin appliance connector. Manufactured from PVC, top screwdriver-released.

**PLUGTOP NYLON**



HW2680831 1
16A

16A three-pin appliance connector. Manufactured from nylon. Top screw fixed.

**PLUGTOP MULTI DIRECT PLUG INN 2X16A**



HW2680866 1
DIRECT PLUG IN

This multiplug creates the option to attach more than one appliance to a plug socket, but limits the total load to 16A. Direct plug-in.


**PLUG MULTI WITH CORD & O/L 5X16A+4X5A**



HW2681519 1

New generation multiplug with 4 sunken Euro type 5A 2 pin, 1 5A 2 pin round lawnmower type and 5 normal 15A 3pin plug points. Total load limited to 16A. With 500mm cord.

**PLUG MULTI SW WITH ILL&CORD+O/L 5X16A+5X5A+EU**



HW2681528 1

New generation multiplug with 4 sunken Euro type 5a 2 pin, 1 5a 2 pin round lawnmower type and 5 normal 15a 3pin plug points. With illuminated on/off switches to activate power points individually. Total load limited to 16a. With 500mm cord.

**PLUG MULTI WITH CORD & O/L 3X16A**



HW2681439 1
3X16A + O\L

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A. With cord of 200mm.

**PLUG MULTI WITH CORD & O/L 5X10A**



HW2681493 1

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A.

**PLUG MULTI WITH CORD CRABTREE**



HW2681531 1
2 X 16A 1SCH

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A.

**COUPLER JANUS DOUBLE PVC 16A**



HW2680847 1
WHITE

To create a customised extension lead and to attach more than one appliance.

**COUPLER JANUS DOUBLE RUBBER**



HW2680858 1
16A

To create a customised extension lead and to attach more than one appliance.

### SWITCH LIGHT THROUGH



| | |
|---|---|
| HW2684423 | 5 |

Ripcord switch to connect or disconnect the electrical circuit.

### SWITCH LIGHT 3L HORISONTAL M.E.S



Versinkte ligskakelaar om 'n stroombaan aan of af te skakel.

### SWITCH LIGHT 3L M.E.S



| | |
|---|---|
| HW2682348 | 1 |
| 1WAY 4X4 WHITE | |

Versinkte ligskakelaar om 'n stroombaan aan of af te skakel.

### SWITCH LIGHT 4L HORISONTAL M.E.S



| | |
|---|---|
| HW2682344 | 1 |
| 1WAY 4X2 WHITE | |

Versinkte ligskakelaar om 'n stroombaan aan of af te skakel.

### SWITCH LIGHT 4L CBI 1WAY



| | |
|---|---|
| HW2682319 | 1 |
| 4X2 WHITE | |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT 4L CBI 1WAY 4X4



| | |
|---|---|
| HW2682320 | 1 |
| WHITE | |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT WITH COVER PLATE 1PACK




| | |
|---|---|
| HW2682265P | 1 |
| 1L 1WAY | |
| HW2682419P | 1 |
| 2L 1WAY | |
| HW2682427P | 1 |
| 1L 2WAY | |
| HW2682559P | 1 |
| 3L 1WAY | |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT 1L 50 X 100 LEAR



| | |
|---|---|
| HW2682843 | 1 |
| 1 WAY | |
| HW2682844 | 1 |
| 2 WAY | |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT BLANK COVERPLATE CBI



| | |
|---|---|
| HW2683745 | 1 |

Coverplate to protect a wiring termination point.

### SWITCH LIGHT 1L CBI 1WAY



| | |
|---|---|
| HW2682315 | 1 |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCHPLUG BLANK COVERPLATE CBI



| | |
|---|---|
| HW2683746 | 1 |

Coverplate to protect a wiring termination point.

### SWITCH LIGHT 1L HORISONTAL M.E.S



Versinkte ligskakelaar om 'n stroombaan aan of af te skakel.

### SWITCH LIGHT 1L M.E.S



Versinkte ligskakelaar om 'n stroombaan aan of af te skakel.

### SWITCH LIGHT 4L M.E.S



| | |
|---|---|
| HW2682349 | 1 |
| 1WAY 4X4 WHITE | |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT BLANK COVERPLATE M.E.S



Dekplaat om 'n draadafsluitingspunt te beskerm.

### SWITCH LIGHT 3L 50 X 100 LEAR



| | |
|---|---|
| HW2682846 | 1 |
| 1 WAY | |

Flush mounted light switch to connect or disconnect a circuit. 10 Year guarantee.

### SWITCH PLUG HORIZONTAL CBI



| | |
|---|---|
| HW2683766 | 1 |
| 4X2 WHITE | |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### SWITCH SOCKET TELEPHONE CBI



| | |
|---|---|
| HW2683806 | 1 |
| 4X2 WHITE | |

Flush mounted telephone socket to connect your telephone with the external cable.

### SWITCH PLUG SINGLE 50 X 100 LEAR



| | |
|---|---|
| HW2682849 | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.


### SWITCH PLUG SINGLE 100 X 100 LEAR



| | |
|---|---|
| HW2682850 | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### SWITCH PLUG CRABTREE



| | |
|---|---|
| HW2682853 | 1 |
| 100X100MM DBL | |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover not included

### SWITCH PLUG COVERPLATE SINGLE CRABTREE



| | |
|---|---|
| HW2682842C | 1 |
| 4X4 | |

Crabtree Classic range switchplug coverplate. How it works: the coverplate is used toghether with the switchplug HW2682842. This product is of high quality. Voltage: 220V to 250V. Product colour: white. Applications: domestic, light industrial. Complete with fitting screws. SABS approved. Product size: 100MM X 100MM.

### SWITCH PLUG INDUSTRIAL



| | |
|---|---|
| HW2683547 | 1 |
| SINGLE 75X100MM | |
| HW2683551 | 1 |
| DUO 75X100MM | |

Surface mount double three-pin wall plug with switches to connect/disconnect a circuit for appliances with a maximum load of 15A.

### SWITCH PLUG CRABTREE



| | |
|---|---|
| HW2682699 | 1 |
| 100X50MM | |
| HW2682842 | 1 |
| 100X100MM | |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover not included.

### SWITCH PLUG VERTICAL CBI



| | |
|---|---|
| HW2683765 | 1 |
| 4X2 WHITE | |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### SWITCH PLUG SINGLE CBI



| | |
|---|---|
| HW2683767 | 1 |
| 4X4 WHITE | |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.


### SWITCHPLUG COVERPLATE CRABTREE



HW2682699C 1
SGL 4X2

Cover plate to cover a switchplug.HW2682699

### GARAGE MOTOR SINGEL TIP UP ALPHA 500 DTS



Electronic motor designed to open and close single garage doors. Upwards action, mainly for wooden garage doors. Soft start and stop control. Anti crush meganism for the protection of vehicles and children. Emergency key release in case of power failure. Can be upgraded to a 12v system. Maximum door surface of 6m² and running distance of 3m. One year warranty. Two remotes included.

### NEXUS ORION SOLAR GARDEN LIGHT S/S



NXS0010

Ni Cad rechargeable battery,1 x White LED,1 x Colour changing LED, Colour selection feature,Glass Lens, Steel Housing, Mounting spike, Day/Night sensor. Amorphous solar panel, 1 year warranty.

### NEXUS SOLAR JAR MEDIUM CLEAR



NXS0011

Specs:
• Ni Cad Rechargeable Battery
• 1 White X LED
• 1 x Colour Changing LED
• Medium Sized Clear Glass Jar
• Steel Handle
• 1 Year Warranty

### NEXUS FLARE SOLAR GARDEN LIGHT S/S



NXS0003 12

Stainless steel housing. Coolwhite LED. Ni-Cad rechargeable battery. 6 hours charging time for 6 hours burning time. Mounting spike. Day/Night sensor. 1 Year warranty.

### NEXUS SOLAR JAR CLEAR SMALL



NXS0013

Specs:
• Ni Cad Rechargeable Battery
• 1 White X LED
• 1 x Colour Changing LED
• Small Sized Clear Glass Jar
• Steel Handle
• Amorphous Solar Panel
• 1 Year Warranty

### NEXUS SOLAR JAR FROSTED SMALL



NXS0014

Specs:
• Ni Cad rechargeable battery
• 1 White X LED
• 1 x Colour Changing LED
• Small Sized Frosted Glass Jar
• Steel Handle
• Amorphous Solar Panel
• 1 Year Warranty

### NEXUS SOLAR LANTERN CANDLE LED SMALL



NXS0015

Specs:
• Ni Cad Rechargeable Battery
• 1 x Amber Flickering LED
• Steel Handle
• Amorphous Solar Panel
• 1 Year Warranty

### NEXUS SOLAR LANTERN CANDLE LED MEDIUM



NXS0016

Specs:
• Ni Cad Rechargeable Battery
• 1 x Amber Flickering LED
• Steel Handle
• Amorphous Solar Panel
• 1 Year Warranty

### NEXUS SOLAR COMBO PACK 6 PIECE



NXS0018

Specs:
• 4 X Mini Stainless Steel Lights
• 2 X Plastic Solar Comets
• Ni Cad Batteries
• Amorphous Solar Panels
• Shrink-wrapped

### NEXUS 10W SOLAR SECURITY LIGHT WITH MOTION SENSOR



NXS0024 1

10W Solar powered floodlight with PIR and day/night that will only activate with motion at night.

Specs:
• 600 Lumen COB Technology
• Aluminium Heavy Duty Construction
• 7.4V 2.2Ah Lithium Ion Battery
• 3W Poly Crystalline Solar Panel
• 5m Cable From Solar Panel To Light
• IP65 Waterproof Rating
• 5-7m Detection Range
• 5-7 Hours Charge Time In Direct Sunlight
• 120 Degree Detection Angle
• 200 x 30 Second Activations – This is purely a reference, the light will remain on for as long as there is movement up to a maximum of 1,6 hours.

### NEXUS SOLAR SECURITY LIGHT 54 LED INC REMOTE



| | |
|---|---|
| NXS0008 | 1 |

Li-Ion 11.4V 4AH Battery. 54 x super bright LED's. 340 Lumens. Aluminium housing. 10W Solar panel. Day/Night sensor. Remote control included. 12 hours running time on full charge. Easy DIY installation. 1 Year warranty.

### NEXUS SOLAR SECURITY LIGHT TWIN WITH PIR SENSOR



| | |
|---|---|
| NXS0006 | 1 |

Specs:
- 2 X LED
- Motion Sensor
- 3.7V 2AH Li-Ion Battery
- 100 Lumens When Activated
- Adjustable Time and Sensitivity
- 2W Solar Panel
- Easy DIY Installation
- 1 Year Warranty

### NEXUS EMERGENCY BACKUP LIGHT 40 SMD LED



| | |
|---|---|
| NXL0100 | 1 |

Specs:
- Latest SMD LED technology
- 320 Lumens
- Up to 9 hours working time
- Can be wall mounted or stand alone
- Carry handle
- Two brightness settings
- Automatically switches on when power goes off
- Charges from 220V power

### NEXUS SOLAR ORNAMENTAL LIGHT



| | |
|---|---|
| NXS0023 | 12 |
| 900MM HIGH, 1 X AAA 150MAH NI-CD | |

Solar ornament light with colour changing LED that consists of a dragonfly, butterfly and sunflower. Stainless steel bottom pole and flexible upper pole. Amorphous solar panel. Minimum order quantity of 12 which will include 4 of each design.


### NEXUS EMERGENCY LANTERN 48 LED WITH USB



| | |
|---|---|
| NXL0105 | 1 |

Specs:
- 390 Lumens
- Up to 8 hours working time
- Adjustable light output
- Can be wall mounted
- Carry handle and hanging hook
- Automatically switches on when power goes off
- Charges from 220V power
- USB output to charge cellphones

### LAMP LED COB 5W GU10 WW NEXUS



| | |
|---|---|
| NXL0004 | 1 |

Latest cob technology, aluminium housing, and very high lumen output.

Specs:
420 Lumens
Warm White
5W
60°
GU10 220V
50 000 Hours
5 Years

### LAMP LED SMD 3X1W GU10 CDL 4PACK NEXUS




| | |
|---|---|
| NXL0006 | 1 |

Value pack, value for money, and efficient lighting.

Specs:
240 Lumens
Cool Day Light
3W
45°
GU10 220V
50 000 Hours
5 Years

### LAMP LED R50 5W CDL NEXUS



| | |
|---|---|
| NXL0014 | 1 |

Ultra bright technology.

Specs:
430 Lumens
Cool Day Light
5W
45°
E14
50 000 Hours
5 Years

**LAMP LED R63 8W CDL NEXUS**



NXL0015 1

Ultra bright technology.

Specs:
700 Lumens
Cool Day Light
8W
45°
E27
50 000 Hours
5 Years

**LAMP LED SMD 4X1W MR16 WW NEXUS**



NXL0012 1

High lumen output, value for money, and every day price fighter (economic option).

Specs:
320 Lumens
Warm White
4W
60°
MR16 12V
50 000 Hours
5 Years

**LAMP LED A60 SMD 8W CDL B22 NEXUS**




NXL0020 1

High lumen output, 270 degree light dispersement.

Specs:
790 Lumens
Cool Day Light
8W
180°
B22
50 000 Hours
5 Years

**LAMP LED SMD 3X1W GU10 WW 4PACK NEXUS**



NXL0008 1

Value pack, value for money, and efficient lighting.

Specs:
240 Lumens
Warm White
3W
45°
GU10 220V
50 000 Hours
5 Years

**LAMP LED COB 5W GU10 CDL NEXUS**



NXL0002 1

Latest cob technology, aluminium housing, and very high lumen output.

Specs:
420 Lumens
Cool Day Light
5W
60°
GU10 220V
50 000 Hours
5 Years

**LAMP LED A60 SMD 8W CDL E27 NEXUS**



NXL0019 1

High lumen output, 270 degree light dispersement.

Specs:
790 Lumens
Cool Day Light
8W
180°
E27
50 000 Hours
5 Years

**LAMP LED PAR38 15W COB CDL NEXUS**



NXL0001 1

Latest cob technology with a very high lumen output.

Specs:
1100 Lumens
Cool Day Light
15W
120°
PAR38/E27
50 000 Hours
5 Years

**LAMP LED SMD 4X1W MR16 CDL NEXUS**



NXL0010 1

High lumen output, value for money, and every day price fighter (economic option).

Specs:
320 Lumens
Cool Day Light
4W
60°
MR16 12V
50 000 Hours
5 Years

### CIRCUIT BREAKER 19MM 4.5KA 1PHASE 40A



| | |
|---|---|
| HW2682899<br>40A | 1 |
| HW2682900<br>50A | 1 |
| HW2682901<br>63A | 1 |

Single phase circuit breakers.Complies with SABS and NRCS regulations.

### CIRCUIT BREAKER ISOLATOR 38MM 3KA 2PHASE



| | |
|---|---|
| HW2682889<br>63A | 1 |

A non-automatic flushed circuit breaker and used as geizer disconnector. It is fully rated and carries the associated circuit breaker fault current for 10 ms.

### CIRCUIT BREAKER19MM 4.5KA 1PHASE+N(Combo)



| | |
|---|---|
| HW2682903<br>63A | 1 |

Single phase circuit breakers.Complies with SABS and NRCS regulations. 10 year guarantee.

### EARTH LEAKAGE 2.5KA 1 PHASE SAM



| | |
|---|---|
| HW2684204<br>60A 230V | 1 |

An automatic switching device capable of sensing earth leakage currents, also capable of interrupting overloads after a defined time period.

### EARTH LEAKAGE 2.5KA 3PHASE SAM



| | |
|---|---|
| HW2684209<br>60A 230V | 1 |

An automatic switching device capable of sensing earth leakage currents, also capable of interrupting overloads after a defined time period.

### DISTRIBUTION BOX WEATHERPROOF SAMITE



| | |
|---|---|
| HW2684461<br>6MOD | 1 |

Surface mount or semi-flush mount weatherproof distribution board accommodating electrical switchgear mounted on mini rail.

### DISTRIBUTION BOARD FLUSH ADJUST SAM



| | |
|---|---|
| hw2684445<br>8MOD | 1 |
| HW2684446<br>12MOD | 1 |
| HW2684449<br>16MOD | 1 |
| HW2684453<br>20MOD | 1 |

Flush adjustable distribution board accommodating electrical switchgear mounted on mini rail.

### DB READY BOARD WIRING ACC BULKHEAD CBI



| | |
|---|---|
| HW2684456 | 1 |

Readyboard complete with switches and bulkhead light fitting. Switches have a glow-in-the-dark fluorescent insert. Compatible with prepayment meters. Suitable for many applications eg. residentail, commercial and industrial applications.

### ELECTRIC FENCE BOBBIN DTS BLACK



| | |
|---|---|
| HW2677000 | 1 |

Bobbins manufactured from plastic, are used for the free standing electric fencing, tied with binding wire to the Y-standard.

### CABLE CABTYRE



| | |
|---|---|
| HW2680702<br>3 CORE WHITE 1.0MM 50M (P/ROLL) | 1 |
| HW2680708<br>3 CORE BLACK 1.0MM 50M (P/ROLL) | 1 |
| HW2680713<br>3 CORE WHITE 1.5MM 50M (P/ROLL) | 1 |
| HW2680719<br>3 CORE BLACK 1.5MM 50M (P/ROLL) | 1 |
| HW2680724<br>3 CORE WHITE 2.5MM 50M (P/ROLL) | 1 |
| HW2680728<br>3 CORE BLACK 2.5MM 50M (P/ROLL) | 1 |
| HW2680751<br>3 CORE WHITE 1.5MM 100M (PM) | 100 |
| HW2680803<br>2 CORE WHITE 1.5MM 100M (PM) | 100 |
| HW2680807<br>3 CORE WHITE 1.0MM 100M (PM) | 100 |
| HW2680807P<br>3 CORE WHITE 1.0MM 5M PACK | 1 |
| HW2680815<br>3 CORE BLACK1.0MM 100M (PM) | 100 |
| HW2680819<br>3 CORE WHITE 2.5MM 100M (PM) | 100 |
| HW2680821<br>3 CORE BLACK 2.5MM 100M (PM) | 100 |
| HW2680836<br>3 CORE BLACK 1.5MM 100M (PM) | 100 |
| HW2680841<br>3 CORE WHITE 1.5MM 100M (PM) | 100 |
| HW2680845<br>3 CORE BLACK 1.0MM 10M PACK | 1 |
| HW2680849<br>3 CORE WHITE 1.0MM 10M PACK | 1 |

High conductivity bunched copper conductors, insulated and colour-coded with general-purpose flexible grade PVC. Cores are then twisted together for maximum flexibility and sheathed with soft flexible grade PVC in circular configuration.

## CABLE EARTH BARE COPPER




| | |
|---|---|
| HW2680274<br>2.5MM 5KG (P/ROLL=234m) | 1 |

High conductivity annealed stranded copper conductors, uninsulated. Used as earth wire by electrical contractors, electricians and municipalities.

## CABLE FLAT



| | |
|---|---|
| HW2679000<br>1.0MMX2+E 100M (PM) | 100 |
| HW2679027<br>1.5MMX2+E 100M (PM) | 100 |
| HW2679032<br>2.5MMX2+E 100M (PM) | 100 |
| HW2680292<br>1.5MMX2+E 50M (PACK ) | 1 |
| HW2680293<br>2.5MMX2+E 50M (PACK ) | 1 |
| HW2680294<br>CABLE FLAT 1.5MMX2+E 20M (PACK ) | 1 |

High conductivity solid or stranded plain copper wire. Insulated and colour-coded with general purpose grade PVC. These insulated cores together with a bare copper earth wire are then sheathed with flexible grade PVC in a flat parallel configuration.

## EARTH LEAKAGE 38MM 4.5KA 2FASE



| | |
|---|---|
| HW2682905<br>63A | 1 |

An automatic switching device capable of sensing earth leakage currents. Also capable of interrupting overloads after a defined time period.

## CABLE RIPCORD




| | |
|---|---|
| HW2680548<br>0.5MM WHITE 100M (PM) | 100 |
| HW2680548P<br>0.5MM WHITE 5M (PACK ) | 1 |
| HW2680560<br>0.5MM CLEAR 100M (PM) | 100 |
| HW2680567<br>0.5MM BLACK 100M (PM) | 100 |
| HW2680567P<br>0.5MM BLACK 5M (PACK ) | 1 |
| HW2680572<br>0.5MM BROWN 100M (PM) | 100 |
| HW2680572P<br>0.5MM BROWN 5M (PACK ) | 1 |
| HW2680581<br>0.5MM CLEAR 10M (PACK ) | 1 |
| HW2680593<br>0.5MM BROWN 10M (PACK) | 1 |

High conductivity bunched plain flexible copper wire, insulated in a parallel configuration with flexible grade PVC, with a colour stripe on one core for polarity indication. Plain white ripcord has a ridge for polarity indication. Price per 1m. Packsize

## CABLE SURFIX ABERDARE



| | |
|---|---|
| HW2680201<br>1.5MMX2+E 100M (PM) | 100 |
| HW2680208<br>1.5MMX3+E 100M (PM) | 1 |
| HW2680213<br>2.5MMX2+E 100M (PM) | 100 |
| HW2680219<br>2.5MMX3+E 100M (PM) | 100 |
| HW2680290<br>PACK 1.5MMX2+E 50M | 1 |
| HW2680291<br>PACK 2.5MMX2+E 50M | 1 |

High conductivity solid or stranded plain copper wire. Insulated with hard grade PVC, covered in an aluminum foil in contact with the tinned earth wire and bonded to a sheath. Colour coded.

## CABLE JOINING



| | |
|---|---|
| HW2660342<br>MX1 METALPLAST | 1 |
| HW2660349<br>MX2 METALPLAST | 1 |

Resin-based low-tension cable splicing kit. Used with cable size up to 4 x 16mm. Voltage rating 1,1 kV.

## CABLE ELECTRIC PVC



| | |
|---|---|
| HW2679292<br>RED/ROOI 1.5MM X 10M | 1 |
| HW2679294<br>BLACK/SWART 1.5MM X 10M | 1 |
| HW2679296<br>BLUE/BLOU 1.5MM X 10M | 1 |
| HW2679298<br>GRN & YELL/GROEN & GEEL 1.5MM X | 1 |
| HW2679332<br>BLUE/BLOU 2.5MM X 20M | 1 |
| HW2679333<br>GREEN/GROEN 2.5MM X 20M | 1 |

High conductivity annealed stranded copper wire in variety of colours. General purpose house wire. Pre-packed to eliminate the cutting of cable and the shrinkage associated with cutting.

## LAMP CFL 15W 3U B22 WW EUROLUX



EU-G159
800lms Lifetime 6000 hrs 2700K

## LAMP CFL 11W 3U B22 WW EUROLUX



EU-G161
550lms Lifetime 6000 hrs

## LAMP CFL 20W 3U E27 CW EUROLUX



EU-G1
1155lms Lifetime 6000 hrs 4000K

## LAMP CFL 15W E27 DAY/NIGHT EUROLUX




EU-G227
800lms Lifetime 6000 hrs 4000K

### LAMP CFL 9W 3U E27 CW EUROLUX



EU-G352
450lms Lifetime 6000 hrs 4000K

### LAMP CFL PL 11W CW BP EUROLUX



EU-G131
720lms Lifetime 8000 hrs 4000K

### LAMP CFL 20W 3U B22 CW EUROLUX



EU-G2
1155lms Lifetime 6000 hrs 4000K

### LAMP CFL 11W E27 DAY/NIGHT CW EUROLUX




EU-G397
550lms Lifetime 6000 hrs

### GATE WHEEL ROLLER SET DTS



| | |
|---|---|
| HW2678072<br>60MM | 1 |
| HW2678073<br>80MM | 1 |

V- grooved gate wheel set consisting of 2 x guide rollers complete with bolt & nuts and 2 x mild steel rollers on bearings fitted in bracket. The rollers can either be welded to the motor gate or fitted with 2 x bolts (7mm). Application mainly for motor gates. Comply with SABS standards. Product carries 1 year gaurantee. No maintenance required.

### LAMP CANDLE CFL 3W E14 WW BP EUROLUX




EU-G142BP
120lms Lifetime 6000 hrs

### LAMP CFL 20W 3U E27 WW EUROLUX



EU-G209
1155lms Lifetime 6000 hrs 4000K1155lms

### LAMP CFL 15W 3U B22 CW EUROLUX



EU-G4
800lms Lifetime 6000 hrs 4000K

### LAMP CFL 15W E27 YELLOW SENSOR EUROLUX




EU-G193
800lms Lifetime 6000 hrs

### LAMP PL 18W 4PIN CW EUROLUX



EU-G629
900lms Lifetime 8000 hrs 4200K

### LAMP MAXIGLOBE CFL 18W 105MM EUROLUX

IMAGE COMING SOON

EU-G24
900lms Lifetime 6000 hrs 4000K

### LAMP CFL 11W 12V DC E27 EUROLUX

IMAGE COMING SOON

EU-G13

**TUBE FLUORESCENT 18W 600MM EUROLUX**



EU-G42
1480lms Lifetime 15 000 hrs 4000K

**LAMP REFLECTOR CFL R63 8W CW EUROLUX**




EU-G374
250lms Lifetime 6000 hrs 4200K

**LAMP SPIRAL R9W7S 9W CW EUROLUX**




EU-G619BP
360lms Lifetime 6000 hrs 4000K

**LAMP CFL SPIRAL 85W E27 CW EUROLUX**



EU-G384BP
4800lms Lifetime 6000hrs 6400K

**LAMP TUBE 2D 28W 4PIN EUROLUX**




EU-G31
2090lms Lifetime 8000 hrs Cool White

**LAMP REFLECTOR CFL R50 7W E14 CW EUROLUX**




EU-G507
150lms Lifetime 6000 hrs 4200K

**LAMP CFL SPIRAL 12W E27 RED EUROLUX**




EU-G433RD
100lms Lifetime 6000 hrs

**LAMP CFL SPIRAL 12W B22 BLUE EUROLUX**




EU-G434BL
50lms Lifetime 6000 hrs

**TUBE FLUORESCENT 58W 1500MM EUROLUX**



EU-G182
5300lms Lifetime 15 000 hrs 4000K

**LAMP REFLECTOR R80 100W E27 EUROLUX**



EU-G76
Candela 480 Lifetime 1000 hrs 2700K

**LAMP CFL SPIRAL 12W E27 CW BP EUROLUX**




EU-G431BP
600lms Lifetime 6000 hrs 4000K

**LAMP PAR38 80W YELLOW EUROLUX**



EU-G171Y
Lifetime 1000 hrs

### LAMP PAR38 80W GREEN EUROLUX



EU-G171GN
Lifetime 1000 hrs

### LAMP PAR38 80W BLUE EUROLUX



EU-G171BL
Lifetime 1000 hrs

### GARAGE MOTOR SINGLE ROLL UP DTS 12



HW2678077 1

Electronic motor designed to open and close single garage doors. It's mainly used for steel roll up garage doors. Smooth and quiet operation. Automatic safety reverse/automatic door stop. Manual override in case of power failure. Maximum of 50kg pulling force. One year warranty. Two remotes included.

### LAMP LED A60 FILAMENT 6W WW E27 NEXUS



NXL0017 1

Latest filament led technology, 360 degree light dispersement, high lumen output.

Specs:
580 Lumens
WARM WHITE
6W
360°
E27
50 000 Hours
5 Years

### LAMP PAR38 150W EUROLUX



EU-G100
Candela 3100 Lifetime 2000 hrs 2700K

### LAMP PAR38 CFL E27 BLUE EUROLUX



EU-G181BL
180lms Lifetime 6000 hrs

### GATE MOTOR RACK NYLON DTS



HW2678014 2
PER 1M

The racks that the gate motor is mounted on to with which the driving gear on the gate motor move the gate. The racks are supplied in lenghts of 1m. Special high impact nylon are used for this.

### LAMP LED A60 FILAMENT 6W WW B22 NEXUS



NXL0018 1

Latest filament led technology, 360 degree light dispersement, high lumen output.

Specs:
580 Lumens
Warm White
6W
360°
B22
50 000 Hours
5 Years

### LAMP PAR38 CFL E27 YELLOW EUROLUX



EU-G181Y
200lms Lifetime 6000 hrs

### LAMP INSECT KILLER 10W BP EUROLUX



EU-G314BP

### GATE MOTOR REMOTE DTS



HW2678044 1
4 BUTT TX4 GREY

Transmitter contains 4 buttons and can therefore be used for 4 different applications for example: 1 gate motor and 3 garage door motors.

### LAMP LED CANDLE FILAMENT 3W WW E14 NEXUS



NXL0016 1

Latest filament led technology, 360 degree light dispersement, high lumen output.

Specs:
360 Lumens
Warm White
3W
360°
E14
50 000 Hours
5 Years

### LAMP LED CANDLE SMD 4W WW E14 NEXUS



NXL0021 1

Great replacement for 40W incandescent candle.

Specs:
350 Lumens
Warm White
4W
160°
E14
50 000 Hours
5 Years

### LAMP OVEN 2PACK E14 40W EUROLUX




EU-G508
300lms Lifetime 1000 hrs 2700K

### LAMP PYGMY 2PAK E14 15W EUROLUX




EU-G509
100lms Lifetime 1000 hrs 2700K

### LAMP LED SMD 4X1W GU10 WW NEXUS



NXL0013 1

High lumen output, value for money, and every day price fighter (economic option).

Specs:
320 Lumens
Warm White
4W
60°
GU10 220V
50 000 Hours
5 Years

### LAMP LED COB 5W MR16 WW NEXUS



NXL0005 1

Latest cob technology, aluminium housing, and very high lumen output.

Specs:
420 Lumens
Warm White
5W
60°
MR16 12V
50 000 Hours
5 Years

### LAMP LED COB 5W MR16 CDL NEXUS



NXL0003 1

Latest cob technology, aluminium housing, and very high lumen output.

Specs:
420 Lumens
Cool Day Light
5W
60°
MR16 12V
50 000 Hours
5 Years

### LAMP HALOGEN GU10 50W LOOSE EUROLUX



EU-G95
Candela 800 Lifetime 2000 hrs 2700K

### LAMP HALOGEN GU10 50W 10P EUROLUX




EU-G504
Lifetime 2000 hrs 2700K

### LAMP LED SMD 4X1W GU10 CDL NEXUS



NXL0011 1

High lumen output, value for money, and every day price fighter (economic option).

Specs:
320 Lumens
Cool Day Light
4W
60°
GU10 220V
50 000 Hours
5 Years

### LAMP QI HALOGEN 100W BP 78MM EUROLUX

IMAGE COMING SOON

EU-G479BP
1300lms Lifetime 2000 hrs 2900K

### LAMP QI HALOGEN 240W BP 118MM EUROLUX




EU-G427
5400lms Lifetime 2000 hrs 2700K

**LAMP QI HALOGEN 400W 118MM LOS EUROLUX**



EU-G189
9000lms Lifetime 2000 hrs 2700K

**LAMP LED A65 10W B22 WARM WHITE EUROLUX**




EU-G924
850lms Lifetime 30 000 hrs 3000K

**LAMP LED 4W GOLFBALL E27 WARM WHITE EUROLUX**




EU-G933
340lms Lifetime 30 000 hrs 3000K

**LAMP LED 6W F-GU10 4000K EUROLUX**




EU-G665CW
360lms Lifetime 15 000 hrs 5500K

**LAMP MERCURY B22 160W EUROLUX**



EU-G168
2800lms Lifetime 6000 hrs 3600K

**LAMP LED A60 6W E27 WARM WHITE EUROLUX**




EU-G926
485lms Lifetime 30 000 hrs 3000K

**LAMP LED 4W CANDLE B22 WARM WHITE EUROLUX**




EU-G931
340lms Lifetime 30 000 hrs 3000K

**LAMEP LED 6W GU10 3000K EUROLUX**




EU-G666WW
300lms Lifetime 15 000 hrs

**LAMP LED A60 6W B22 COOL WHITE EUROLUX**




EU-G929
485lms Lifetime 30 000 hrs 4000K

**LAMP LED A60 E27 DAY/NIGHT 8W CW EUROLUX**




EU-G761CW
485lms Lifetime 30 000 hrs 6000K

**LAMP LED 4W CANDLE E14 WARM WHITE EUROLUX**




EU-G932
340lms Lifetime 30 000 hrs 3000K

**LAMP LED GU10 7W DIMMABLE LAMP CW 6000K EUROLUX**



EU-G727CW
500lms Lifetime 30 000 hrs 6000K

### LAMP LED T8 TUBE 12W 600MM CDL NEXUS



NXL0022 1

High lumen, ultra bright, retro-fit.

Specs:
1000 Lumens
Cool Day Light
12W
120°
G13
50 000 Hours
5 Years

### LAMP LED T8 TUBE 24W 1200MM CDL NEXUS




NXL0023 1

High lumen, ultra bright, retro-fit.

Specs:
2000 Lumens
Cool day Light
24W
120°
G13
50 000 Hours
5 Years

### NEXUS EMERGENCY BACKUP LIGHT 108 SMD LED



NXL0103 1

Specs:
• Latest SMD LED technology
• 900 Lumens
• Up to 9 hours working time
• Can be wall mounted
• Carry handle and hanging hook
• Two brightness settings
• Pull string activation
• Automatically switches on when power goes off
• Charges from 220V power

### NEXUS EMERGENCY LANTERN 39 SMD LED



NXL0104 1

Specs:
• Latest SMD LED technology
• 400 Lumens
• Up to 8 hours working time
• Adjustable light output
• Can be wall mounted
• Carry handle and hanging hook
• Automatically switches on when power goes off
• Charges from 220V power
• Backup AA battery compartment for additional light time

### NEXUS EMERGENCY BACKUP LIGHT 48 SMD LED



NXL0101 1

Specs:
• Latest SMD LED technology
• 390 Lumens
• Up to 12 hours working time
• Can be wall mounted or stand alone
• Carry handle and hanging hook
• Two brightness settings
• Automatically switches on when power goes off
• Charges from 220V power

### NEXUS EMERGENCY BACKUP LIGHT 72 SMD LED



NXL0102 1

Specs:
• Latest SMD LED technology
• 600 Lumens
• Up to 12 hours working time
• Can be wall mounted or stand alone
•Carry handle and hanging hook
• Two brightness settings
• Pull string activation
• Automatically switches on when power goes off
• Charges from 220V power

### BULKHEAD ROUND WITH GRID EUROLUX



EU-B110B
Rustproof IP: 44 Class 2.

### LIGHT BABY EMPEROR ES MATELEC CLEAR




HW2672154 1

Energy saving light fitting ideal for outdoor use. Not reccomended for use in housing estates. Lamp can easily be removed without loosening screw's. Suited to all weather conditions. Suited for E27 energy saver lamp with screw base.

### LIGHT MIRAGE VISOR ES MATELEC OPAL




HW2672151 1

Energy saving light fitting ideal for outdoor use. Suited for all weather conditions. Suited for E27 energy saver lamp with screw base.

### LIGHT EMPEROR MATELEC CLEAR




HW2672157 1
2DX28W

Energy saving light fitting ideal for outdoor use. Suited for all weather conditions. Suited for 2D X 28 W energy saver lamp.

### LIGHT CENTURION HIGH VISOR ES MATELEC OPAL




HW2672156 1

Energy saving light fitting ideal for outdoor use. Stainless steel screws. Heavy duty construction. Suited for all weather conditions. Suited for E27 energy saver lamp with screw base.

### LIGHT CEILING ALAB 400MM E27 EUROLUX



EU-C49SC

IP 20 Depth 120mm Diameter 400mm Steel

### LIGHT CEILING RUST 2X60W EUROLUX



EU-C57R

IP 20 Depth 130mm Diameter 370mm Steel

### LIGHT CEILING ROPESTYLE 47CM EUROLUX



EU-C62R

IP 20 Depth 150mm Diameter 480mm Steel

### LIGHT SQUARE ALUM BASE



HW2672145 1

BC 100W WHT

Modern industrial bulkhead light fitting. High visor, square light. UV stabilised, polycarbonate lens with white die cast aluminium powder coated base. BC 220V lamp holder. Clear see through lens. Suitable for indoor, outdoor and industrial use. Ideal for agricultural application. Use with BC type globe. Splash proof. Complete with BC light fitting. SABS approved. Robust lens. IP55 Weather proof rating. Light size 190mm x 190mm. Should be fitted by an approved electrician. Bulkhead with polycarbonate lens can be used to burn continuously.

### LIGHT CENTURION DAY/NIGHT SWITCH



HW2672160 1

2D 16W OPAL

Modern slimline multi-purpose, daylight sensor energy saving light fitting. UV stabilised polycarbonate lens. 2D 16watt lampholder. Opal colour. Suitable for indoor and outdoor use. Use with 2D globe HW2675130. Complete with stainless steel fixing screw

### LIGHT GALAXY MATELEC



HW2672165 1

ES 60WT OPAL

Modern domed/oyster multipurpose lightfitting. Uv stabilised polycarbonate lens. ES lampholder. Opal colour. Suitable for indoor and outdoor use. Use with ES type globe. Complete with stainless steel fixing screws. SABS approved. IP 65 Weather proof rating. Light size 270mm x 112mm.

### FLOODLIGHT WITH GLASS 400W EUROLUX



EU-FS18B

IP : 44 Die Cast Aluminium

### FLOODLIGHT LED SENSOR BLACK EUROLUX



EU-FS113B

IP : 55 Die Cast Aluminium

### FLOODLIGHT 2X15W CFL E27 EUROLUX



EU-FS35

IP : 54. Class : 1 PVC

### OVAL SMALL EYELID BLACK EUROLUX



EU-B60B

IP 54 H 105mm W 210mm W 95mm

### LIGHT FITTING WATER RESISTANT JAR



HW2682168 1

100W

Incandescent lamp fitting, water resistant, oval glass lamp shade, used as outside house light. Standard jamjar type.

### LIGHT FITTING WATER RESISTANT PVC



HW2682191 1

Rectangular lamp fitting accommodating 60 W incandescent lamp. It is water resistant and is used as an outside house light.

### LIGHT FITTING WATER RESISTANT PVC DAY/NIGHT



HW2682177 1
60W

Rectangular lamp fitting accommodating 60 W incandescent lamp. It is water resistant and is used as an outside house light. Equipped with day/night sensor to automatically switch the light on and off.

### LANTERN WALL 4 PANEL UP BLACK EUROLUX




EU-O14B
IP : 44 H 380mm W 150mm D 190mm

### LANTERN 6 PANEL DOWN BLACK EUROLUX



EU-O18B
IP : 44 H 360mm W 210mm D 210mm

### LANTERN 4 PANEL PILLAR BLACK EUROLUX



EU-O19B
IP : 23 H 430mm W 150mm D 150mm

### SPIKE GARDEN PLASTIC PAR38 EUROLUX



EU-O27B
IP 44 H 250mm D 75mm

### LAMP SHADE BALL GLASS



HW2672076 1
160MM
HW2672079 1
200MM

Ball type lamp shade, made of PVC, with thread to be used with ceiling lamp holder mounting piece manufactured from porcelain, PVC and fibre glass.

### LIGHT LEAD WITH CORD



HW2680882 1
220V

220V. 2m Cable. Bayonet type globe not included. See electric range HW2675013 (60W) and HW2675021 (100W) for globe.

### WORKLIGHT TELESCOPIC 1X500W EUROLUX



EU-FS3
IP : 44 H 1890mm W 710mm D 580mm

### LIGHT WALL ALAB E27 CHROME EUROLUX



EU-W55ASC
IP 20 H 150mm W 300mm D 105mm

### LIGHT WALL S/S IP44 EUROLUX



EU-O144SS
IP 44 H 290mm W 230mm W 90mm

### DOWNLIGHT SET STRAIGHT CHROME EUROLUX




EU-D36SC
IP : 22 Includes 1 x Halogen GU10 50W

### DOWNLIGHT SET 3PACK TILT CHROME EUROLUX




EU-D64SC
IP : 22 Includes 3 x Halogen GU10 50W

### DOWNLIGHT SET 3PACK STRAIGHT ALUM EUROLUX




EU-D63SC
IP :22 Includes 3 x Halogen GU10 50W

### FITTING FLUORESCENT 1X18W 2FT EUROLUX



EU-PR36
IP : 20 Epoxy Coated Pressed Steel

### GLANDS POLY



| | |
|---|---|
| HW2660223 | 1 |
| NO0 | |
| HW2660228 | 1 |
| NO1 | |


Used for various unarmored cable size terminations to maintain the sealing of enclosures of specific demanded IP ratings.

### DOWNLIGHT SET 3PACK TILT WHITE EUROLUX



EU-D64W
IP : 22 Includes 3 x Halogen GU10 50W

### LAMP HOLDER DIOCHROIC GU10 INTERNATIONAL LIGHTING



| | |
|---|---|
| HW2672098 | 1 |
| FOR 230V LAMP | |

Downlamp holder bracket for 230V lamp.

### FITTING FLUORESCENT 1X36W 4FT EUROLUX



EU-PR37
IP : 20 Epoxy Coated Pressed Steel

### LAMPHOLDER BRASS



| | |
|---|---|
| HW2682113 | 1 |
| BC 10MM | |

Lamp holder accommodating BC incandescent lamps manufactured from brass material used for pipemount.

### DOWNLIGHT SET STRAIGHT WHITE EUROLUX




EU-D36W
IP : 22 Includes 1 x Halogen GU10 50W

### LAMP HOLDER DIOCHROIC MR16 INTERNATIONAL LIGHTING



| | |
|---|---|
| HW2687111 | 1 |
| FOR 12V LAMP | |

Replacement MR16 - 12V lamp holder - length 20cm.

### LEDSTRIP 5M WARMWHITE EUROLUX




EU-G649WW
Lifetime 30 000 hrs 24W 12V

### LAMPFITTING CEILING FIBREGLASS & PORCELAIN



| | |
|---|---|
| HW2672052 | 1 |
| BC 160MM | |

Ceiling Lamp holder mounting piece manufactured from fibre glass with porcelainLamp holder accommodating 40W to 100W incandescent lamps.

### LAMP HOLDER CORD GRIP NYLON BC



HW2681986 1

Bayonet type 25mm Lamp holder accommodating 40 to 200 W incandescent lamps manufactured from nylon material used directly with cabtyre cable.

### LAMP HOLDER PORCELAIN BC



HW2681993 1

Lamp holder accommodating 40 to 200 W BC incandescent lamps, manufactured from porcelain, normally fitted onto a ceiling Lamp holder mounting piece.

### LAMP HOLDER PORCELAIN PLAIN



HW2681997 1
ES

Lamp holder accommodating 40 to 200 W ES incandescent lamps, manufactured from porcelain, normally fitted onto a ceiling Lamp holder mounting piece. Standard Edison screw type fitting.

### LAMP HOLDER PAR 38 SINGLE WALL MOUNT



HW2682129 1

Lamp holder accommodating a single par 38 incandescent lamp (HW2675175, HW2675179) manufactured from nylon - used for surface mount on various surfaces.

### PLUG MULTI WITH CORD 4X16A+2X5A+EUKO PP1



HW2681501P 1
4X16A-2X5A+EUKO

This multiplug creates the option to attach more than one appliance to a plug socket but limits the total load to 16A. Direct plug-in.

### PLUG MULTI WITH CORD 4X16A+2X5A+EUKO



HW2681501 1
4X16A-2X5A+EUKO

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A.

### PLUG MULTI WITH CORD & O/L 3X16A+2X5A



HW2681513 1

New generation multiplug with 3 sunken Euro type 5a 2 pin and 3 normal 15a 3pin plug points. Total load limited to 16a. With 500mm cord.

### PLUG MULTI T-PIECE DIGITECH



HW2681580P 1
3X16A

HW2681581P 1
1X16A 2X5A

HW2681582P 1
2X16A 2X5A

HW2681583P 1
4X16A 2X5A

HW2681594P 1
3X16 3X5A

HW2681595P 1
4X16A 4X5A 1XSCHUKO

The T-piece multi plug range from Digitech is completely unique in the sense that it plugs directly into the wall socket and eliminates the cable that is always in the way. The plug also has adjustable feet that levels it against the wall en prevents the plug from wobbling. Great quality and value for money.

### PLUGTOP CONVERTOR EUROMATE ROUND TOP ENT



HW2681420 1

Change normal 16A 3 point plugtop to a euro style round 2 point plugtop.

### PLUGTOP MULTI EURO DIRECT PLUG INN 3X5A



HW2681418 1

Multi plug, 3 in 1 Euro type coupling for use in cellphone chargers and other two pin plug 5A. Total load limited to 16A.

### PLUGTOP MULTI DIRECT PLUG INN 3X16A



HW2680873 1

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A.

### PLUGTOP EUROMATE TOP ENTRY 5A



| | |
|---|---|
| HW2681407 | 1 |
| 5A | |

Converting a two-point plug to a 16A three-pin connector.

### PLUGTOP MULTI EURO ADAPTOR CRABTREE



| | |
|---|---|
| HW2681529 | 1 |
| 2 X 16A | |
| HW2681530 | 1 |
| 4 X 16A | |

Crabtree slimline compact adaptor for domestic. The adaptor is used toghether with the plug HW2680824. This product is of high quality. Voltage: 220V. Exterior body white. SABS approved. The benefits of the new plug can be enjoyed with the matching range of adapters, without having to replace excisting wall sockets. In addition to its space-savings benefits and superior looks, the new compact 3-pin plug is very user-friendly.

### PLUGTOP MULTI DIRECT PLUG INN 1X16A+2X5A



| | |
|---|---|
| HW2681404 | 1 |

Create the option to attach more than one appliance to a plug socket but limiting the total load to 16A.

### CONDUIT ADAPTOR FEMALE SABS



| | |
|---|---|
| HW2685357 | 5 |
| 20MM | |

Used to form a link between conduit pipe and a suitable accessory. Loose.

### CONDUIT INSPECTION T PIECE SABS



| | |
|---|---|
| HW2685558 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations, with a inspection lid which can be removed to inspect the electrical wiring. Loose.

### CONDUIT COUPLING SABS



| | |
|---|---|
| HW2685418 | 10 |
| 20MM | |

Used to link two pieces of conduit pipe together. Loose.

### CONDUIT BOX 3 WAY SABS



| | |
|---|---|
| HW2685167 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations. Loose.

### CONDUIT BOX LID SABS 20MMX50MM



| | |
|---|---|
| HW2685264 | 5 |

Conduit box lid.

### CONDUIT BOX 1 WAY SABS



| | |
|---|---|
| HW2685078 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations. Loose.

### CONDUIT BOX 4 WAY SABS



| | |
|---|---|
| HW2685213 | 1 |
| 20MM | |

Used to re-route electrical wiring to its required terminations. Loose.

### CONDUIT SADDLE GALVANISED



| | |
|---|---|
| HW2685309 | 10 |
| 20MM | |

Manufactured from galvanised sheets. Used to fix conduit on vertical and horizontal surfaces at predetermined points. Loose.

### CONDUIT SADDLE SABS PVC



| | |
|---|---|
| HW2685302 | 10 |
| 20MM | |

Manufactured from PVC. Used to fix conduit on vertical and horizontal surfaces at predetermined points. Loose.

### WALL BOX GALVANISED



| | |
|---|---|
| HW2684929 100X50MM | 1 |
| HW2684932 100X100MM | 1 |

Flush mount wall box, manufactured from galvanised sheets, accommodates all flush mount switches and plugs. Loose.

### EXTENSION BOX WHITE



| | |
|---|---|
| HW2684896 100X50MM | 1 |
| HW2684900 100X100MM | 1 |

Surface mount wall box, manufactured from cold rolled sheets and painted white, accommodates all flush mount switches and plugs. Loose.

### CONDUIT BENDING SPRING



| | |
|---|---|
| HW2684839 20MM | 1 |

A spring with a outside diameter to fit inside a rigid conduit pipe with a 20mm diameter. Used to bend rigid conduit smoothly without folding the pipe.

### CONDUIT PVC GLUE




| | |
|---|---|
| HW2684841 200ML | 1 |

A glue designed to weld two pieces of PVC fittings together to make them weatherproof.

### NEXUS AURORA SOLAR GARDEN LIGHT S/S



| | |
|---|---|
| NXS0001 | 20 |

Stainless steel housing. 1 x Coolwhite LED. Ni-Cad rechargeable battery. Mounting spike. 6 hours charging time for 6 hours burning time. Day/Night sensor. 1 Year warranty.

### NEXUS GEMINI SOLAR GARDEN PATH LIGHT 6 PACK



| | |
|---|---|
| NXS0005 | 6 |

Li-Ion Battery. Stainless steel housing. 1 x super bright LED. 10 Lumen high power light output. Glass lens. Lithium Ion battery. 6 hours charging time for 6 hours burning time. Day/Night sensor. Mounting spike. Comes in a gift pack of two. 1 Year warranty.

### NEXUS COMET SOLAR GARDEN SPOTLIGHT PLASTIC



| | |
|---|---|
| NXS0002 | 12 |

Ni-Cad rechargeable battery. 3 x Coolwhite LED's. Day/Night sensor. Plastic housing. Adjustable head angle and solar panel. Ideal for the lighting of trees, plants and walls. Mounting spike. 1 Year warranty.

### NEXUS LUNAR ORB SOLAR GARDEN LIGHT S/S



| | |
|---|---|
| NXS0004 | 20 |

Glass lens. Colour changing LED. Ni-Cad rechargeable battery. 6 hours charging time for 6 hours burning time. Stainless steel housing. Mounting spike. Day/Night sensor. 1 Year warranty.

### SOLAR PARTY LIGHT 9 PACK



| | |
|---|---|
| NXS0017 | |

Specs:
- 1 X Colour Changing LED
- Frosted Plastic Lens
- 1 X 150 MAH Ni Cad Battery
- Silver Finish
- 9 Pack

### NEXUS SOLAR LIGHT PIR PLASTIC 50 LUMENS



| | |
|---|---|
| NXS0019 | 1 |

Specs:
- 3 X LED
- Motion Sensor
- 1 X 3.2V 250 MAH Li-Ion Battery
- 2,5 Lumens On Standby
- 50 Lumens When Activated
- 40 Hours On Standby
- 120 Minutes On 50 Lumens = 240 Activations Of 30sec
- 10m Activation Distance
- 1 Year Warranty

### NEXUS SOLAR WALL LIGHT PIR S/S 200 LUMENS



| | |
|---|---|
| NXS0020 | 1 |

Specs:
- 10 X Super Bright LED's
- Motion Activated
- Frosted Glass Lens
- 1 X 3.7V 2000mah Li-Ion Battery
- Standby - 10 Lumens
- Activated - 200 Lumens (200 x Brighter Than Traditional Garden Light)

### NEXUS SOLAR PATH LIGHT WITH SENSOR S/S 100 LUMENS



NXS0021 1

Specs:
• 5 Super Bright LED's
• Motion Activated
• Glass Lens
• 1 X 3.2V 400mah Li-Ion Battery
• Standby - 8 Lumens
• Activated - 100 Lumens (100 x Brighter than traditional Garden Light)

### NEXUS SOLAR LAMP POST 60/200 LUMENS ALUM



NXS0022 1

Specs:
• Die Cast Aluminium Pole and Base
• Steel Lamp Head
• Glass Lens
• 60 Lumen Setting
• 200 Lumens Setting
• 1 X 2000mah 3.7V Lion Battery

### NEXUS SOLAR JAR MEDIUM FROSTED



NXS0012

Specs:
• Ni Cad Rechargeable Battery
• 1 White X LED
• 1 x Colour Changing LED
• Medium Sized Frosted Glass Jar
• Steel Handle
• Amorphous Solar Panel
• 1 Year Warranty

### NEXUS SOLAR SECURITY LIGHT 60 LED PIR SENSOR



NXS0007 1

Specs:
• 60 X LED
• Motion Sensor
• 3.7V 2AH Li-Ion Battery
• 180 Lumens When Activated
• Adjustable Time and Sensitivity
• 2W Solar Panel
• Easy DIY Installation
• Wide angle
• 1 Year Warranty

### NEXUS SOLAR SECURITY LIGHT 108 LED INC REMOTE



NXS0009 1

Li-Ion 11.4V 8AH Battery. 108 x super bright LED's. 550 Lumens. Aluminium housing. 20W Solar panel. Day/Night sensor. Remote control included. 12 hours running time on full charge. Easy DIY installation. 1 Year warranty.

### SWITCH LIGHT DIMMER CBI 4X2 WHITE



HW2682876 1

Lightswitch with the option to adjust the brightness of lamps.

### ISOLATOR STOVE COVERPLATE CRABTREE



HW2684241C 1

Crabtree Classic range switchplug coverplate. The coverplate is used together with the switchplug at code HW2684241. High quality product. Voltage: 220V to 250V. Product colour: white. Applications: domestic, light industrial. Complete with fitting screws. SABS approved. Product dimensions: 100MM X 100MM.

### ISOLATOR STOVE CRABTREE PP1




HW2684241P 1
1L.30A SM PP1

A non-automatic flushed circuit breaker and used as stove isolator.

### SWITCH LIGHT 3L CBI 1WAY



HW2682318 1
4X2 WHITE

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT 6L CBI 1WAY 4X4



HW2682321 1
WHITE

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH BELL CBI



HW2682310 1
4X2 WHITE

Flush mounted doorbell switch to to activate doorbell.

### SWITCH LIGHT CRABTREE



HW2682265 1
1L 1WAY

HW2682419 1
2L 1WAY

HW2682427 1
1L 2WAY

HW2682559 1
3L 1WAY

Flush mounted light switch to connect or disconnect a circuit. Cover not included.

### SWITCH LIGHT INDUSTRIAL 75X75MM



| | |
|---|---|
| HW2683113<br>1L | 1 |
| HW2683117<br>2L | 1 |
| HW2683407<br>3L | 1 |

Surface mounted switch to connect or connect or disconnect a circuit.

### SWITCH LIGHT COVERPLATE CRABTREE



| | |
|---|---|
| HW2682265C<br>1LEVER 1WAY 4X2 | 1 |
| HW2682419C<br>2LEVER 1 WAY 4X2 | 1 |

Cover plate to protect a wiring termination point.

### SWITCH LIGHT 2L 50 X 100 LEAR



| | |
|---|---|
| HW2682845<br>1 WAY | 1 |

Flush mounted light switch to connect or disconnect a circuit.

### SWITCH LIGHT 1L CBI 2WAY



| | |
|---|---|
| HW2682316 | 1 |

Flush mounted light switch to connect or disconnect a circuit. Used to switch light on or off at both ends of the passage.

### SWITCH PLUG DOUBLE 100 X 100 LEAR



| | |
|---|---|
| HW2682851 | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.


### SWITCH PLUG WITH COVER PLATE DUO PP1 CRABTREE




| | |
|---|---|
| HW2682853P<br>100X100MM | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A.

### SWITCH PLUG COVERPLATE CRABTREE



| | |
|---|---|
| HW2682853C<br>DUO 4X4 | 1 |

Cover plate to cover a switchplug HW2682842.

### SWITCH PLUG EURO HORIZONTAL CBI



| | |
|---|---|
| HW2683785<br>4X2 WHITE | 1 |

Flush mount three-pin and two euro wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### SWITCH PLUG EURO VERTICAL CBI



| | |
|---|---|
| HW2683786<br>4X4 WHITE | 1 |

Flush mount three-pin and two euro wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### SWITCH PLUG DOUBLE CBI



| | |
|---|---|
| HW2683768<br>4X4 WHITE | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A. Cover included.

### CABLE TIES



| | |
|---|---|
| AO763/0006<br>92MMX2.6MM (100) | 1 |
| AO763/0007<br>140MMX3.6MM (100) | 1 |
| AO763/0008<br>197MMX4.9MM (100) | 1 |
| AO763/0009<br>267MMX4.8MM (100) | 1 |
| AO763/0010<br>381MMX4.9MM (100) | 1 |
| AO763/0011<br>385MMX7.6MM (X50) | 1 |

Multi-purpose use. Bulk pack cable ties.

### INSULATION TAPE NITTO



| | |
|---|---|
| HW2660124<br>BLACK 20M | 1 |
| HW2660129<br>BLUE 20M | 1 |
| HW2660132<br>YELLOW 20M | 1 |
| HW2660137<br>GREEN 20M | 1 |
| HW2660142<br>RED 20M | 1 |
| HW2660148<br>WHITE 20M | 1 |

Is both a cold and weather resistant electrical tape, coated with an aggressive rubber resin adhesive with good aging characteristics. Extremely flexible, even in cold weather and unaffected by moisture and most chemicals. No flagging or deterioration even under temperatures between -18 and 80 °C.

### ELEMENT GEYSER SPANNER



| | |
|---|---|
| HW2682749 | 1 |

Spanner specifically designed to easily install and maintain single circuit heating elements used normally with warm water geysers.

### THERMOSTAT GEYSER



| | |
|---|---|
| HW2682751<br>VKF7 650W-1KW | 1 |
| HW2682759<br>VK11 2-4KW | 1 |

Designed to control the temperature of a domestic electric water heater. It incorporates a built-in fuse link to ensure that the safe, maximum temperature for hot water cylinders cannot be exceeded.

### ELEMENT GEYSER THERMOSTAT SOCKET PP1



Single circuit heating element for domestic hot water cylinders. It incorporates a pocket to accept the VKF type thermostat. Used in "normal" or non-aggressive water. Available in bulk and prepacks.

### VALVE PACK BRASS GEYSER



| | |
|---|---|
| LSG0007A<br>400KPA | 1 |

Supplied with 400kPa pressure valve, 2 vacuum valves and stop tap.


### VALVE TEMPERING INLINE 15MM FOR SOLAR GEYSER.



| | |
|---|---|
| LSV0101A | 1 |

Inline tempering valve temp preset to 43°C. Inner diameter changed to 15mm to allow for easy connection.

### GEYSER BLANKET UNIVERSAL KIT



| | |
|---|---|
| LSB1010A<br>3.5M x 1.25M | 1 |

Geyser blankets are made with aluminium laminated SABS material and is recommended by Eskom. This blanket fits all makes and sizes for inside and outside use. Can also be used with cold- or hot water pipes. Material is UV treated. No special tools required. Dimensions: 3.4 m x 1.25 m plus 5 m alumuminium adhesive tape.

### PUMP DIAPHRAGM TRIPLEX MINI DC 12V



| | |
|---|---|
| 302FL40 | 1 |

Ideal for camping, boating, cattle and game spraying. Self priming and for intermittent use only.

### INSULATION TAPE BLACK QUALITY



| | |
|---|---|
| AO762/0205<br>10M | 1 |
| AO762/0240<br>20M | 1 |

Top quality tape for warm and cold isolation.

### SOLAR WARM WATER NON PRESSURE SYSTEM 100L



| | |
|---|---|
| LSS0100L<br>100L | 1 |

Solar geyser system SABS and Eskom approved, with 100L tank capacity. Non pressurised solar water system, no electrical connections. Total water capacity 146L. Inner tank material 0,5mm stainless steel SU 304-2B. Supplied with filler tank and ball valve for water cut-off. Filler tank capacity 12L. Unit supplied with copper alloy floating valve, stainless steel ball valve, pressure release vent and galv steel frame for mounting. Vacuum tube outer glass 3.3mm, hail resistant to 25mm, freeze protect to -20°C. Total number of tubes 16 x 1,8M length, outer tube 58MM, inner tube 47mm. Escom Q-factor 16.395 MJ/m2. Guarantee of 5 years on storage tank, feeder tank, vacuum tubes, frame, silicone rubbers and plastic support cones. Balance 1 year guarantee. SABS approved, permit number 9387/14897. With installation by Eskom approved plumber this unit qualifies for Eskom rebate structures.

### GEYSER TRAY



| | |
|---|---|
| LSG0001A<br>100lt | 1 |
| LSG0002A<br>150lt & 200lt | 1 |
| LSG0003A<br>250lt & 300lt | 1 |

Used in case geyser leaks or burst to prevent further damage.

### ELEMENT GEYSER SPIRAL SOFT WATER



| | |
|---|---|
| ELK-140-KWI<br>4KW 200L | 1 |
| HW2682770<br>2KW 100L | 1 |
| HW2682772<br>3KW 150L | 1 |

Domestic geyser element with brass Euro type boss, rating 230V. Soft water type, application Kwikot type geysers 50L to 200L. Use thermostat type TSE11, HW262783.

### THERMOSTAT QUICK TERM



| | |
|---|---|
| HW2682783<br>TSE11 | 1 |

Designed to control the temperature of domestic electric geysers. For use with Kwikot type geyser elements HW2682770 and HW2682772.

### ELEMENT GEYSER HARD WATER



| | |
|---|---|
| HW2682734<br>2KW 100L HARD WATER | 1 |
| HW2682741<br>3KW 200L HARD WATER | 1 |
| HW2682746<br>4KW 300L HARD WATER | 1 |

Single circuit heating element specially designed for areas where the water supply is hard or corrosive and where standard copper sheathed elements are not suitable. The sheath material is Incoloy 825, which has a corrosion resistance much superior.

### SWITCH PLUG WITH COVER PLATE 1PACK




| | |
|---|---|
| HW2682699P<br>100X50MM | 1 |
| HW2682842P<br>100X100MM | 1 |

Flush mount three-pin wall plug with a switch to connect/disconnect a circuit for appliances with a maximum load of 15A.

### GATE MOTOR KIT 12V DTS



| | |
|---|---|
| HW2678000<br>500 KG | 1 |

Electronic motor to open and close gates. The motor can operate a weight of up to 500kg gates. Soft start and stop control. Programmable opening for pedestrians. 12V 7.2Amp hour battery backup in case of power failure is supplied free of charge. The speed of the gate is 18m/min. The gate motor is mainly for domestic use. Anti crush mechanism for the safety of vehicles and children. Two year warranty on mechanics and one year warranty on electronics. The kit consist of 1x motor, baseplate, 12V battery and 2x remotes and 2 x 2meter racks.
Spare Infra red beam safety switch at HW2678007 Spare Rack at HW2678014.

### CONDUIT SABS PVC



| | |
|---|---|
| HW2684845<br>4MX20MM | 25 |
| HW2684848<br>4MX25MM | 1 |

Rigid PVC pipe with a 20/25mm diameter. Used to convey electrical wiring from one designated point to another, adhering to SABS specifications.

### CONDUIT ADAPTOR MALE SABS



| | |
|---|---|
| HW2685353<br>20MM | 10 |

Used to form a link between conduit pipe and a suitable accessory. Loose.


### PUMP SOLAR



| | |
|---|---|
| 302DC4524C<br>POMP DC 45-24 45M | 1 |

Brushless submersible pumps with a height from 45m or 70m. Pumps available in 3 different sizes: 12V, 24V and 36V. Pump is powered directly from the solar panel, via a selfregulting controller. Positive displacement pump. Kit includes two solar panels for the 302DC4524C and 302DC4536C- models and one solar panel for the 302DC7012C model and an MPPT controller.


### PUMP SOLAR SUBMERSIBLE S2000



| | |
|---|---|
| 302SS2022<br>SS022 PUMP | 1 |
| 302SS2042<br>SS042 PUMP | 1 |
| 302SS2101<br>SS101 PUMP | 1 |
| 302SS2151<br>SS151 PUMP | 1 |

All Sun-Sub systems are supplied complete with pump element, variable speed DC brushless submersible motor and MPPT (Maximum Power Point Tracker) solar motor controller. The Progressing Cavity (PC) pump element used in borehole applications is proven to provide maximum water output in a variety of water conditions. The Sun-Sub is suitable for a 100mm (4") borehole. Systems from 525 Watts to 700 Watts, drawing its energy from the sun, thus eliminating the need for diesel or AC power. The solar pump will slow down when it is cloudy, but because it has no minimum speed (unlike a centrifugal pump) it will keep delivering water.


### PUMP SOLAR SUBMERSIBLE S1000



| | |
|---|---|
| 302SS1022<br>SS022 PUMP | 1 |
| 302SS1041<br>SS041 PUMP | 1 |
| 302SS1061<br>SS061 PUMP | 1 |

All Sun-Sub systems are supplied complete with pump element, variable speed DC brushless submersible motor and MPPT (Maximum Power Point Tracker) solar motor controller. The Progressing Cavity (PC) pump element used in borehole applications is proven to provide maximum water output in a variety of water conditions. The Sun-Sub is suitable for a 100mm (4") borehole. Systems from 175 Watts to 2800 Watts, drawing its energy from the sun, thus eliminating the need for diesel or AC power. The solar pump will slow down when it is cloudy, but because it has no minimum speed (unlike a centrifugal pump) it will keep delivering water.

### PUMP SOLAR SUBMERSIBLE S3000



| | |
|---|---|
| 302SS3022<br>SS022 PUMP | 1 |
| 302SS3042<br>SS042 PUMP | 1 |
| 302SS3062<br>SS062 PUMP | 1 |
| 302SS3101<br>SS101 PUMP | 1 |
| 302SS3151<br>SS151 PUMP | 1 |

All Sun-Sub systems are supplied complete with pump element, variable speed DC brushless submersible motor and MPPT (Maximum Power Point Tracker) solar motor controller. The Progressing Cavity (PC) pump element used in borehole applications is proven to provide maximum water output in a variety of water conditions. The Sun-Sub is suitable for a 100mm (4") borehole. Systems from 875 Watts to 2800 Watts, drawing its energy from the sun, thus eliminating the need for diesel or AC power. The solar pump will slow down when it is cloudy, but because it has no minimum speed (unlike a centrifugal pump) it will keep delivering water.

### DISPLAY UNIT HANDHELD



| | |
|---|---|
| 302DISPLAY | 1 |

The hand held display unit is a diagnostic tool.

### PUMP SURFACE SUNRAY



| | |
|---|---|
| 302SRX0025<br>CP25 | 1 |
| 302SRX0800<br>CP800 | 1 |
| 302SRX1600<br>CP1600 | 1 |

All Sun-Ray systems are supplied complete with pump element, variable speed DC brushless motor and MPPT (Maximum Power Point Tracker) solar motor controller.Designed to transfer water efficiently and reliably from sources such as fountains, rivers, tanks and dams. The highly efficient Progressing Cavity (PC) pump is self-priming. The high suction lift allows for the pump to be installed on the top of dam walls or on river-banks above the high water mark. Systems from 175 Watts to 1400 Watts, drawing its energy from the sun, thus eliminating the need for diesel or AC power. The solar pump will slow down when it is cloudy, but because it has no minimum speed (unlike a centrifugal pump) it will keep delivering water.